



HJ5-50

HJ5-50, HELIAX® Standard Air Dielectric Coaxial Cable, corrugated copper, 7/8 in, black PE jacket

Construction Materials

Jacket Material	PE
Dielectric Material	PE
Flexibility	Standard
Inner Conductor Material	Copper tube
Jacket Color	Black
Outer Conductor Material	Corrugated copper

Dimensions

Nominal Size	7/8 in
Cable Volume	3.5 ft ³ /kft 325.2 L/km
Cable Weight	0.80 kg/m 0.54 lb/ft
Diameter Over Jacket	28.194 mm 1.110 in
Inner Conductor OD	9.1440 mm 0.3600 in
Outer Conductor OD	25.400 mm 1.000 in

Electrical Specifications

Cable Impedance	50 ohm ±0.5 ohm
Capacitance	22.2 pF/ft 72.8 pF/m
dc Resistance, Inner Conductor	0.820 ohms/km 0.250 ohms/kft
dc Resistance, Outer Conductor	0.656 ohms/km 0.200 ohms/kft
dc Test Voltage	6000 V
Inductance	1.870 µH/m 0.570 µH/ft
Insulation Resistance	100000 Mohms•km
Jacket Spark Test Voltage (rms)	8000 V
Operating Frequency Band	1 – 5200 MHz
Peak Power	90.0 kW
Power Attenuation	2.781
Velocity	92%

Environmental Specifications

Installation Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Storage Temperature	-70 °C to +85 °C (-94 °F to +185 °F)

General Specifications

Brand	HELIAX®
-------	---------

Mechanical Specifications

Bending Moment	33.9 N-m 25.0 ft lb
----------------	-----------------------



HJ5-50

Flat Plate Crush Strength	250.0 lb/in 4.5 kg/mm
Minimum Bend Radius, Multiple Bends	254.00 mm 10.00 in
Number of Bends, minimum	15
Number of Bends, typical	20
Pressurization, maximum	0 N/mm ² 30 psi
Tensile Strength	363 kg 800 lb

Standard Conditions

Attenuation, Ambient Temperature	20 °C 68 °F
Average Power, Ambient Temperature	40 °C 104 °F
Average Power, Inner Conductor Temperature	100 °C 212 °F

Attenuation

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)	Average Power (kW)
0.5	0.082	0.025	90.00
1	0.116	0.035	78.44
1.5	0.143	0.043	63.98
2	0.165	0.05	55.36
10	0.372	0.113	24.56
20	0.529	0.161	17.26
30	0.65	0.198	14.03
50	0.846	0.258	10.79
88	1.134	0.346	8.05
100	1.212	0.369	7.53
108	1.262	0.385	7.23
150	1.499	0.457	6.09
174	1.621	0.494	5.63
200	1.746	0.532	5.23
300	2.168	0.661	4.21
400	2.532	0.772	3.60
450	2.7	0.823	3.38
500	2.86	0.872	3.19
512	2.897	0.883	3.15
600	3.161	0.963	2.89
700	3.442	1.049	2.65
800	3.708	1.13	2.46
824	3.769	1.149	2.42
894	3.946	1.203	2.31
960	4.107	1.252	2.22
1000	4.203	1.281	2.17
1250	4.77	1.454	1.91
1500	5.296	1.614	1.72
1700	5.694	1.735	1.60
1800	5.886	1.794	1.55
2000	6.26	1.908	1.46
2100	6.442	1.964	1.42
2200	6.621	2.018	1.38
2300	6.798	2.072	1.34
2500	7.142	2.177	1.28
2700	7.478	2.279	1.22
3000	7.965	2.428	1.15
3400	8.592	2.619	1.06
3700	9.045	2.757	1.01
4000	9.488	2.892	0.96
5000	10.893	3.32	0.84

* Values typical, guaranteed within 5%

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system